

TIG400 (P)

EN SERIES

NGEN EMPOWERING FUTURE

TIG400 (P) EN

DC Pulse TIG/MMA Welding Machine 400A / 3 Phase 380V



SPECIFICATION

Model	NGEN-TIG400 (P) (EN)
Input Power Supply	AC380V +15%, 50/60Hz
Max Input Capacity (kVA)	MMA 13.3 / TIG 13.2
Welding Current / Duty Cycle	MMA 320A/60%, TIG 400A/60%
No-load Voltage (V)	70
Welding Current Range (A)	MMA 20 to 320 / TIG 10 to 400
Arc Force (A)	0 to 100
Protection Class	IP21S
Insulation Class	F
Dimensions L x W x H (mm)	320 x 530 x 260

DC Pulse	●
2T / 4T	●
HF TIG	●
MMA	●

STANDARD ACCESSORIES

- TIG torch with consumables
- Earth clamp with cable
- Gas hose

Product Features

- Three phase 380V: industrial supply for heavy duty TIG and MMA work.
- DC pulse TIG: pulse control for better heat input management on thin or heat sensitive material.
- 2T/4T trigger control: choose 2T for short welds or 4T for long runs without holding the trigger.
- HF TIG: high frequency arc start for clean ignition.
- MMA welding: stick welding mode for general fabrication.



Designed in CANADA
Built to Last

NGEN INDUSTRIES INCORPORATED
100 Matheson Boulevard East Mississauga
Ontario Canada
www.ngen-global.com